

THE ULTIMATE SOLUTION FOR ALL RE-BAR TYING WORK

RE-BAR-TIER™ RB650A

MAX

RE-BAR TYING SYSTEMS

BENEFITS

● REDUCES TYING TIME

About 5 times faster than manual tying. Make ties in approx. 1 sec. per tie with consistent tie strength. High speed tying saves you time and money.

● REDUCES RISK OF HEALTH PROBLEMS

Just pulling the trigger. The simple operation reduces potential wrist damage such as carpal tunnel injuries. Using the optional extension bar reduces the risk of back injuries.




Carpal tunnel syndrome



Extension bar (Option)

● 16 GA. TIE WIRE



The combination of 16 gauge tie wire and a powerful twisting motor insures a perfect tie every time. Wire usage is regulated automatically to match the size of the tie and increase productivity. One roll of wire ties 120 to 230 ties.

● TIES UP TO #9 x #8 RE-BARS

● ONE HAND OPERATION

Allows worker to hold re-bar while tying, reducing set up time.

APPLICATIONS



COMMERCIAL BUILDINGS / FOUNDATIONS / ROAD CONSTRUCTION / BRIDGES
PRECAST PLANTS / RADIANT HEATING TUBES



Up to #9 x #8 re-bars

Cooling fan

Torque adjustment dial

Tie wire (16 gauge)
120 - 230 ties / coil

Trigger lock

Nickel metal hydride high capacity battery (3.3 Ah, 9.6 V)
30 minute quick recharge

STANDARD EQUIPMENT

- 2 Batteries ● Battery charger
- Case ● Holster
- Instructional video tape (English & Spanish)



Holster

TIE WIRE 16 ga. 50 coils / box

TW1525: Regular Steel wire



TW1525-EG: Electro Galvanized wire



TW1525-PC: Polyester-Coated wire



- US Patent Pending

SPECIFICATIONS

MODEL	RB650A
WEIGHT	7.2 lbs.
DIMENSIONS	13-1/8" x 4" x 14-1/2"
TYING SPEED	Approx. 1 second / tie
TIES PER COIL	120 - 230 ties / coil
TIES PER CHARGE	2 - 3 coils / charge
MAXIMUM BAR SIZE COMBINATION	#9 x #8
BATTERY	JP509H (Ni-Mh Battery)
VOLTAGE	DC 9.6V (3.3 Ah)
RECHARGE TIME	Approx. 30 minutes

The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



MAX USA CORP.

257 East 2nd Street Mineola, New York 11501
Phone: 800-223-4293 Fax: 516-741-3272
www.maxusacorp.com

Dealer: