

FORM RELEASE 7000

FORM RELEASE 7000 is a VOC compliant, chemical release for concrete forms that effectively prevents bonding of concrete to plastic, steel, aluminum, treated paper forms and plywood. FORM RELEASE 7000 is composed of organic chemicals that react with the concrete to prevent adhesion and provide a guick and easy release.

ADVANTAGES:

- FORM RELEASE 7000 produces a smooth, unstained architectural concrete surface ready for curing compounds, sealers, mastics or paints when applied according to manufacturers instructions.
- Waterproofs mill oiled plywood forms to prevent the wicking of alkaline water from the concrete into the form, preventing the form from rotting out and raising the grain, thus doubling or tripling form life.
- Protects metal forms by chemically reacting and forming a rustproof film.
- Makes pre-manufactured forms self-cleaning and reduces maintenance costs by as much as 50%.
- FORM RELEASE 7000 leaves no residue or cement dust on the concrete surface, so concrete is left with an architectural surface ready for application of curing compound, sealer or bonder for plaster, mastics or paint. When any material is to be applied on top of the concrete, follow the application instructions of the material manufacturer.
- Makes forms virtually self-cleaning; if sprayed daily, equipment can be cleaned in a minimal amount of time.

COMPLIES WITH:

- Federal E.P.A. VOC compliant contains less then 250 g/l
- Corps of Engineers CEGS-03300, section 10.8 form coating
- Navy Dock and Piers 56359

COVERAGE:

- Rough Sawn, Dimensional and Striated Plywood.......800-1000 Sq. Ft./Gal.
- Two coats recommended for porous surfaces at 500 sq. ft. per gallon and 800 sq. ft. per gallon for subsequent pours.

TECHNICAL:

- FORM RELEASE 7000 is a thin amber liquid consisting of organic chemicals that react with the concrete to prevent adhesion.
- FORM RELEASE 7000 is free of diesel or kerosene.

PHYSICAL PROPERTIES	•
---------------------	---

Flash Point.....>295 °F

Freezing/Melting Pt....-65 °F

APPLICATION:

- Forms should be free from dirt, hardened concrete and foreign matter.
- Release agent is ready to use direct from container.
- Apply a thin film using a Scotchman fog tip.
- Spray uniformly with cross spray to avoid holes and uncoated areas.
- Avoid over application.
- Prior to coating plywood forms, apply one or two heavy brush coats to edges for waterproofing protection.

CAUTION:

- For industrial use only
- Keep out of reach of children
- Do not cut top off drum with torch
- Keep away from heat or open flame
- Avoid prolonged breathing of vapors
- Avoid prolonged or repeated skin contact

CLEAN-UP:

• Sprayers and other equipment may be cleaned with a solvent degreaser.

AVAILABLE PACKAGING:

- 55 gallon drums
- 5 gallon pails

LIMITATIONS:

- When any material is to be applied over the newly formed concrete, follow the application instructions of the material manufacturer.
- Do not use on reinforcing steel. Concrete will not bond to the steel.
- Not a tilt-up bond breaker.

Limited Warranty: Greenstreak warrants its products to be free of manufacturing defects and that they will meet Greenstreak's current published physical properties when applied in accordance with Greenstreak's directions and tested in accordance with ASTM and Greenstreak's standards. There are no other warranties by Greenstreak of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Greenstreak shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty, whether expressed or implied, including any warranty of merchantability or fitness for a particular purpose or from any other cause whatsoever. Greenstreak shall also not be responsible for use of this product in a manner to infringe on any patent held by others.



3400 Tree Court Industrial Blvd. St. Louis, MO 63122 Phone (636) 225-9400 or (800) 325-9504 Fax (636) 225-2049 or (800) 551-5145 Greenstreak.com • E-mail: info@greenstreak.com